



# SK12B THRU SK110B

## 1.0 AMPS. Surface Mount Schottky Barrier Rectifiers



Voltage Range  
20 to 100 Volts  
Current  
1.0 Amperes


### Features

- ✧ For surface mounted application
- ✧ Metal to silicon rectifier, majority carrier conduction
- ✧ Low forward voltage drop
- ✧ Easy pick and place
- ✧ High surge current capability
- ✧ Plastic material used carriers Underwriters Laboratory Classification 94V-O
- ✧ Epitaxial construction
- ✧ High temperature soldering:  
260°C / 10 seconds at terminals

### Mechanical Data

- ✧ Case: Molded plastic
- ✧ Terminals: Solder plated
- ✧ Polarity: Indicated by cathode band
- ✧ Packaging: 16mm tape per EIA STD RS-481
- ✧ Weight: 0.093 gram

### SMB/DO-214AA



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SK 12B	SK 13B	SK 14B	SK 15B	SK 16B	SK 110B	Units	
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	50	60	100	V	
Maximum RMS Voltage	$V_{RMS}$	14	21	28	35	42	70	V	
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	50	60	100	V	
Maximum Average Forward Rectified Current at $T_A=75^\circ\text{C}$	$I_{(AV)}$	1.0						A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	30						A	
Maximum Instantaneous Forward Voltage @ 1.0A	$V_F$	0.5		0.75		0.85		V	
Maximum DC Reverse Current (Note 1) @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=100^\circ\text{C}$	$I_R$	0.5						mA mA	
		10.0			5.0		1.0		
Typical Thermal Resistance ( Note 1 )	$R_{\theta JL}$	25						$^\circ\text{C}/\text{W}$	
Typical Junction Capacitance (Note 2)	$C_j$	110						pF	
Operating Temperature Range	$T_J$	-55 to +125			-55 to +150				$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150						$^\circ\text{C}$	

Notes: 1. Thermal Resistance from Junction to Lead.

2. Measured at 1.0 MHz and Applies Reverse Voltage of 4.0V.

3. Measured on P.C.Board with 0.4 x 0.4" (10 x 10mm) Copper Pad Areas.

## RATINGS AND CHARACTERISTIC CURVES (SK12B THRU SK110B)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE

